

## Photometric test report

Family  
**Monsun® 21**

Order number: **51FG20DP440BHD**  
EAN: **4058352520390**

LP number  
**59060\_71**



**Version** prismatic diffuser, opal, polycarbonate, wide distribution  
**Lamps** LED 4000 K | CRI ≥ 80  
**Controlgear** ECG-DALI  
**Rated values** Net luminous flux = 4810 lm  
Power consumption = 37.4 W  
Luminous efficacy = 128.6 lm/W

serial  
documentation  
**01.07.2021**


sitEco

Luminous intensity in cd/klm

C180-0

C270-90

Imax: 319 cd/klm



### Classifications

DIN 5040 A 4 1  
CIE N1=45 N2=75 N3=93  
N4=94 N5=100

### Luminaire light output ratios

$\eta_{LB}$  100.0%  
 $\phi_u$  93.7%  
 $\phi_o$  6.3%

### Measurement conditions

DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> <b>Monsun® 21</b>	<b>Order number: 51FG20DP440BHD</b> <b>EAN: 4058352520390</b>	<b>LP number</b> <b>59060_71</b>
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes $\gamma$	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	319.4	319.4	319.4	319.4	319.4	319.4	319.4	1.9	1.9
5°	319.1	317.8	316.0	317.2	318.6	318.6	318.8	15.2	17.1
10°	313.9	312.8	311.0	312.1	313.5	313.5	313.7	29.8	46.9
15°	305.6	304.7	302.7	303.7	305.0	304.9	305.2	43.2	90.1
20°	294.3	293.5	291.4	292.2	293.3	293.1	293.5	54.9	145.0
25°	280.9	280.2	277.7	277.9	278.8	278.5	278.8	64.6	209.6
30°	265.9	265.3	262.4	261.6	261.9	261.4	261.7	72.0	281.6
35°	249.2	248.5	245.6	243.7	242.9	242.2	242.4	77.0	358.5
40°	231.6	230.8	227.5	224.6	222.7	221.4	221.6	79.5	438.0
45°	212.9	211.8	208.5	204.2	201.3	199.0	199.4	79.5	517.5
50°	193.7	192.3	188.8	183.7	179.4	175.9	176.0	77.3	594.9
55°	174.1	172.4	168.8	162.7	157.2	152.3	152.1	73.1	667.9
60°	153.8	152.1	148.1	141.4	134.9	128.8	127.5	66.9	734.9
65°	133.1	131.4	127.0	119.9	112.8	105.5	102.8	59.2	794.0
70°	112.0	110.4	105.0	98.0	90.2	82.2	78.2	49.9	843.9
75°	90.5	88.8	83.0	75.7	67.3	58.8	53.6	39.3	883.2
80°	69.4	67.4	62.0	54.0	45.3	36.4	30.4	28.3	911.6
85°	51.2	49.1	43.8	35.9	26.7	17.7	11.3	18.6	930.2
90°	40.3	38.3	33.0	25.3	16.4	7.5	1.9	12.9	943.1
95°	36.9	35.1	30.2	22.8	14.1	5.6	1.6	11.6	954.7
100°	33.7	31.9	27.1	20.1	11.9	4.0	1.5	10.1	964.8
105°	30.1	28.5	23.8	17.3	9.5	2.6	1.3	8.6	973.4
110°	26.5	24.6	20.5	14.4	7.3	1.5	1.2	7.1	980.4
115°	22.8	21.1	17.3	11.6	5.2	1.3	1.2	5.7	986.1
120°	19.1	17.5	14.1	8.9	3.4	1.3	1.1	4.4	990.5
125°	15.4	13.9	10.8	6.2	1.7	1.2	1.0	3.2	993.6
130°	11.8	10.5	7.7	3.9	1.4	1.2	1.0	2.2	995.8
135°	8.3	7.2	5.0	2.0	1.4	1.2	1.1	1.4	997.2
140°	5.1	4.3	2.5	1.6	1.3	1.1	1.0	0.8	998.0
145°	2.4	2.0	1.8	1.6	1.4	1.2	1.2	0.5	998.5
150°	1.9	1.9	1.8	1.5	1.4	1.3	1.2	0.4	999.0
155°	1.8	1.8	1.6	1.5	1.4	1.3	1.3	0.4	999.3
160°	1.6	1.6	1.5	1.5	1.4	1.4	1.3	0.3	999.6
165°	1.5	1.5	1.4	1.4	1.4	1.4	1.3	0.2	999.8
170°	1.4	1.4	1.4	1.4	1.4	1.4	1.3	0.1	999.9
175°	1.3	1.3	1.3	1.4	1.4	1.4	1.3	0.1	1000.0
180°	1.3	1.3	1.3	1.3	1.3	1.3	1.3	0.0	1000.0

## Photometric test report

<b>Family</b> Monsun® 21	<b>Order number: 51FG20DP440BHD</b> <b>EAN: 4058352520390</b>	<b>LP number</b> 59060_71
-----------------------------	--	------------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	19.6	21.3	19.9	21.6	21.9	19.4	21.1	19.7	21.4	21.7
	3H	21.4	22.9	21.8	23.3	23.6	20.9	22.5	21.3	22.8	23.2
	4H	22.2	23.7	22.6	24.0	24.4	21.5	23.0	21.9	23.4	23.7
	6H	22.9	24.3	23.3	24.7	25.0	22.0	23.3	22.4	23.7	24.1
	8H	23.3	24.5	23.7	24.9	25.3	22.1	23.4	22.5	23.8	24.2
	12H	23.5	24.8	24.0	25.1	25.6	22.2	23.4	22.6	23.8	24.2
4H	2H	20.3	21.8	20.7	22.1	22.5	20.2	21.6	20.5	22.0	22.3
	3H	22.3	23.6	22.7	24.0	24.4	21.9	23.2	22.3	23.6	24.0
	4H	23.3	24.4	23.7	24.8	25.3	22.6	23.8	23.1	24.2	24.6
	6H	24.1	25.1	24.6	25.6	26.0	23.2	24.2	23.6	24.6	25.1
	8H	24.5	25.5	25.0	25.9	26.4	23.3	24.3	23.8	24.7	25.2
	12H	24.9	25.7	25.4	26.2	26.7	23.4	24.3	23.9	24.8	25.2
8H	4H	23.6	24.5	24.1	25.0	25.5	23.1	24.0	23.5	24.4	24.9
	6H	24.6	25.4	25.1	25.9	26.4	23.7	24.5	24.2	25.0	25.5
	8H	25.1	25.8	25.6	26.3	26.8	24.0	24.7	24.5	25.2	25.7
	12H	25.6	26.2	26.1	26.7	27.3	24.2	24.8	24.7	25.3	25.8
12H	4H	23.7	24.5	24.1	25.0	25.4	23.2	24.0	23.6	24.4	24.9
	6H	24.7	25.4	25.2	25.9	26.4	23.9	24.6	24.4	25.1	25.6
	8H	25.3	25.9	25.8	26.4	26.9	24.2	24.8	24.7	25.3	25.8


<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm:</b>	<b>L = 1590</b>	<b>H(C0) = 21</b>	<b>H(C180) = 21</b>
			<b>B = 87</b>	<b>H(C90) = 21</b>	<b>H(C270) = 21</b>

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>							
		0°	15°	30°	45°	60°	75°	90°	
	180°	165°	150°	135°	120°	105°	90°	270°	
		195°	210°	225°	240°	255°	270°		
		345°	330°	315°	300°	285°			
45°	8435.6	8423.9	8433.4	8510.9	8741.6	9100.6	9675.7		
50°	8138.0	8114.2	8127.0	8183.1	8385.0	8731.2	9371.6		
55°	7849.1	7810.6	7822.3	7845.7	8017.0	8337.0	9048.9		
60°	7540.3	7502.2	7499.1	7498.2	7635.6	7923.5	8669.1		
65°	7215.5	7175.1	7142.2	7119.7	7230.0	7470.9	8221.2		
70°	6846.1	6801.4	6706.4	6665.2	6726.7	6921.7	7669.4		
75°	6394.8	6337.8	6180.2	6084.3	6055.9	6169.2	6867.9		
80°	5868.4	5764.9	5587.2	5346.3	5182.0	5110.0	5672.0		
85°	5438.9	5293.4	5044.1	4680.0	4237.0	3786.7	3923.2		

**Photometric test report**

<b>Family</b> <b>Monsun® 21</b>	<b>Order number: 51FG20DP440BHD</b> <b>EAN: 4058352520390</b>	<b>LP number</b> <b>59060_71</b>
------------------------------------	--	-------------------------------------

**Luminance values in cd/m<sup>2</sup>**     γ 65°   γ 70°   γ 75°   γ 80°   γ 85°     **siteco**



## Photometric test report

Family <b>Monsun® 21</b>	Order number: <b>51FG20DP440BHD</b> EAN: <b>4058352520390</b>	LP number <b>59060_71</b>
-----------------------------	--	------------------------------

<b>Dimming levels table</b>	environmental temperature: 25°C	<b>sITeco</b>
-----------------------------	---------------------------------	---------------

Luminous flux %	Dimming level linear	Dimming level logarithmic	Luminous flux [lm]	Power consumption [W]
100	254	254	4810	37.4
95	240	252	4561	35.6
90	227	250	4326	33.7
85	214	248	4090	32.1
80	201	245	3852	30.3
75	188	243	3613	28.7
70	175	240	3372	27.0
65	162	238	3130	25.2
60	149	234	2886	23.6
55	136	231	2640	22.0
50	124	228	2411	20.5
45	111	224	2162	18.8
40	99	219	1932	17.3
35	86	214	1680	15.7
30	74	209	1448	14.1
25	61	202	1194	12.4
20	49	194	957	11.0
15	37	183	719	9.6
10	25	169	480	8.1
5	13	145	240	6.8
3	8	127	139	6.2