


# Photometric test report

<b>Family</b> Round 21 M	<b>Order number: 51MR36GD0321B</b> <b>EAN: 4058352881606</b>	<b>LP number</b> 59510_20
<b>Version</b>	Suspended luminaire, cover, opal, PMMA, extremely wide distribution, direct-/ indirect distribution, aluminium housing, black, UGR≤22	<b>serial documentation</b> 31.07.2024
<b>Lamps</b>	LED 3000 K   CRI ≥ 80	
<b>Controlgear</b>	ECG-DALI	
<b>Rated values</b>	Net luminous flux = 7550 lm Power consumption = 54.6 W Luminous efficacy = 138.3 lm/W	



**Luminous intensity in cd/klm** C180-0 C270-90 **Imax: 320 cd/klm**



Classifications	
DIN 5040	B 4 3
CIE	N1=49 N2=80 N3=96 N4=85 N5=100

Luminaire light output ratios	
$\eta_{LB}$	100.0%
$\phi_u$	85.0%
$\phi_o$	15.0%

Measurement conditions
DIN EN 13032 and DIN 5032

## Photometric test report

<b>Family</b> Round 21 M	<b>Order number: 51MR36GD0321B</b> <b>EAN: 4058352881606</b>	<b>LP number</b> 59510_20
<b>Table of values for luminous intensities</b>		<b>Maximum luminous intensity</b>
		<b>siteco</b>

C-planes $\gamma$	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
0°	319.5	319.5	319.5	319.5	319.5	319.5	319.5	1.9	1.9
5°	317.7	317.8	317.8	317.7	317.7	317.7	317.7	15.2	17.1
10°	312.3	312.3	312.3	312.2	312.2	312.2	312.2	29.7	46.8
15°	303.3	303.5	303.4	303.3	303.3	303.3	303.2	43.0	89.8
20°	291.2	291.3	291.2	291.2	291.0	291.0	291.0	54.6	144.4
25°	276.2	276.6	276.2	276.3	275.9	276.0	275.9	64.0	208.4
30°	259.0	259.3	259.0	258.9	258.6	258.6	258.5	70.9	279.4
35°	239.6	240.1	239.7	239.7	239.3	239.3	239.1	75.3	354.7
40°	218.9	219.3	218.8	219.0	218.3	218.8	218.1	77.1	431.8
45°	195.8	197.7	196.8	197.2	196.3	196.9	196.0	76.3	508.0
50°	172.9	174.9	174.1	174.4	173.6	174.1	173.3	73.1	581.1
55°	149.7	151.6	150.7	151.3	150.2	150.8	150.0	67.7	648.8
60°	125.8	127.7	126.8	127.4	126.3	126.7	126.1	60.2	709.0
65°	101.1	103.0	102.1	102.9	101.7	102.5	101.5	50.8	759.8
70°	75.9	78.1	77.0	77.8	76.7	77.7	76.5	39.8	799.6
75°	51.2	53.2	52.4	53.1	52.2	53.0	52.1	27.8	827.4
80°	28.4	30.2	29.8	30.3	29.8	30.0	29.7	16.1	843.5
85°	10.5	12.5	12.3	12.9	12.5	12.4	12.2	6.7	850.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	850.3
95°	7.6	7.9	7.6	7.8	7.5	7.5	7.0	4.2	854.4
100°	9.9	10.0	10.0	10.0	9.8	9.8	9.4	5.3	859.7
105°	11.7	11.8	11.8	11.8	11.7	11.7	11.2	6.2	865.9
110°	13.7	13.9	13.9	13.9	13.9	13.7	13.2	7.1	873.1
115°	16.1	16.4	16.4	16.4	16.2	16.1	15.7	8.1	881.1
120°	18.9	19.1	19.2	19.4	19.0	18.9	18.6	9.0	890.2
125°	22.3	22.4	22.3	22.6	22.2	22.1	21.9	10.0	900.2
130°	26.1	26.1	26.0	26.2	25.8	25.9	25.5	10.9	911.1
135°	30.0	30.1	30.1	30.1	30.0	30.0	29.5	11.6	922.7
140°	34.5	34.5	34.7	34.6	34.7	34.6	34.1	12.2	934.9
145°	39.8	39.6	39.8	39.8	39.7	39.7	39.5	12.5	947.4
150°	45.9	45.3	45.7	45.5	46.0	45.9	45.8	12.5	959.9
155°	51.8	51.9	51.7	52.5	52.1	52.4	52.3	12.1	972.0
160°	56.4	56.5	56.5	56.6	56.5	56.5	56.6	10.6	982.6
165°	59.0	59.0	59.0	59.0	59.1	59.1	59.2	8.4	990.9
170°	60.6	60.5	60.6	60.6	60.7	60.7	60.8	5.8	996.7
175°	61.5	61.3	61.3	61.4	61.4	61.4	61.4	2.9	999.6
180°	61.5	61.5	61.5	61.5	61.5	61.5	61.5	0.4	1000.0

## Photometric test report

<b>Family</b> Round 21 M	<b>Order number: 51MR36GD0321B</b> <b>EAN: 4058352881606</b>	<b>LP number</b> 59510_20
-----------------------------	---	------------------------------

<b>UGR-Table</b>	<b>Standard room</b>	<b>siteco</b>
------------------	----------------------	---------------

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	18.4	19.8	18.9	20.3	20.9	18.3	19.7	18.9	20.3	20.9
	3H	19.8	21.1	20.4	21.6	22.3	19.8	21.0	20.4	21.6	22.3
	4H	20.4	21.6	21.0	22.2	22.9	20.4	21.6	21.0	22.2	22.8
	6H	20.8	21.9	21.4	22.5	23.2	20.9	21.9	21.5	22.5	23.2
	8H	20.9	21.9	21.5	22.5	23.2	20.9	21.9	21.6	22.6	23.3
	12H	21.0	21.9	21.6	22.6	23.3	21.0	22.0	21.7	22.6	23.3
4H	2H	19.0	20.2	19.6	20.8	21.5	19.0	20.2	19.6	20.8	21.4
	3H	20.7	21.7	21.3	22.3	23.0	20.7	21.7	21.3	22.3	23.0
	4H	21.4	22.3	22.0	22.9	23.6	21.4	22.3	22.0	22.9	23.6
	6H	21.9	22.7	22.6	23.3	24.1	21.9	22.7	22.6	23.3	24.1
	8H	22.0	22.7	22.7	23.4	24.2	22.0	22.7	22.7	23.4	24.2
	12H	22.1	22.8	22.8	23.4	24.2	22.2	22.8	22.9	23.5	24.3
8H	4H	21.6	22.3	22.3	23.0	23.8	21.6	22.3	22.3	23.0	23.8
	6H	22.2	22.8	22.9	23.5	24.3	22.2	22.8	22.9	23.5	24.3
	8H	22.4	23.0	23.1	23.7	24.5	22.4	23.0	23.2	23.7	24.5
	12H	22.6	23.1	23.4	23.8	24.6	22.7	23.1	23.4	23.8	24.6
12H	4H	21.7	22.3	22.4	23.0	23.8	21.7	22.3	22.4	23.0	23.8
	6H	22.3	22.8	23.0	23.5	24.3	22.3	22.8	23.0	23.5	24.3
	8H	22.6	23.0	23.3	23.7	24.5	22.6	23.0	23.3	23.7	24.6

<b>Luminance table</b>	<b>Max. for <math>\gamma \geq 65^\circ</math></b>	<b>Photometric dimensions in mm:</b>	<b>D = 590</b>
------------------------	---	--------------------------------------	----------------

C-planes	$\gamma$	Luminance in cd/m <sup>2</sup>							
		0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	
45°		7648.1	7720.2	7686.5	7701.7	7665.3	7691.0	7654.1	
50°		7429.8	7514.8	7478.2	7493.2	7456.1	7481.2	7443.5	
55°		7209.7	7300.7	7256.5	7283.5	7233.3	7258.5	7219.8	
60°		6949.9	7053.0	7001.0	7036.4	6974.5	6995.2	6962.2	
65°		6607.1	6733.0	6670.1	6725.1	6644.6	6696.8	6631.9	
70°		6128.3	6308.3	6215.4	6283.0	6189.5	6271.8	6177.6	
75°		5464.2	5675.9	5590.0	5663.0	5570.9	5656.4	5562.5	
80°		4515.1	4806.9	4740.7	4813.2	4734.7	4774.6	4715.8	
85°		3332.7	3950.5	3895.7	4095.0	3945.8	3930.9	3872.9	

**Photometric test report**

<b>Family</b> Round 21 M	<b>Order number: 51MR36GD0321B</b> <b>EAN: 4058352881606</b>	<b>LP number</b> 59510_20
-----------------------------	---	------------------------------

**Luminance values in cd/m<sup>2</sup>**

$\gamma$  65°   
   $\gamma$  70°   
   $\gamma$  75°   
   $\gamma$  80°   
   $\gamma$  85°

**siteco**

