


Photometric test report

Family Round 21 M	Order number: 51MR36ND0421W EAN: 4058352829967	LP number 59653_7
Version	Suspended luminaire, micro prismatic cover, PMMA, wide distribution, direct-/ indirect distribution, aluminium housing, white, UGR≤19	serial documentation 31.07.2024
Lamps	LED 4000 K CRI ≥ 80	
Controlgear	ECG-DALI	
Rated values	Net luminous flux = 7470 lm Power consumption = 54.6 W Luminous efficacy = 136.8 lm/W	



Luminous intensity in cd/klm C180-0 C270-90 **Imax: 459 cd/klm**



Classifications	
DIN 5040	B 5 3
CIE	N1=66 N2=90 N3=98 N4=84 N5=100

Luminaire light output ratios	
η_{LB}	100.0%
ϕ_u	84.0%
ϕ_o	16.0%

Measurement conditions
DIN EN 13032 and DIN 5032

Photometric test report

Family Round 21 M	Order number: 51MR36ND0421W EAN: 4058352829967	LP number 59653_7
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	Luminous intensity in cd/klm							Luminous flux in lm/klm	
	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
0°	459.1	459.1	459.1	459.1	459.1	459.1	459.1	0.1	0.1
1°	458.3	458.6	458.2	459.2	458.5	459.2	458.6	0.9	1.0
2°	458.4	458.7	458.0	458.1	458.4	458.6	459.0	1.8	2.7
3°	458.2	457.6	457.3	457.8	457.5	457.7	458.0	2.6	5.4
4°	456.3	456.8	456.8	457.2	456.0	457.0	456.1	3.5	8.9
5°	455.2	455.6	455.6	455.4	454.9	455.3	455.2	4.4	13.2
6°	453.9	454.5	454.0	454.2	453.3	454.1	454.1	5.2	18.4
7°	451.8	452.6	452.0	452.1	452.0	452.3	451.3	6.0	24.5
8°	450.4	450.9	450.4	450.6	450.1	450.9	449.2	6.9	31.3
9°	447.6	448.4	447.6	448.2	446.8	448.4	447.7	7.7	39.0
10°	445.2	446.0	445.3	445.8	444.5	445.7	444.6	8.5	47.5
11°	441.5	443.4	442.4	442.5	441.3	443.1	441.0	9.3	56.8
12°	438.9	440.2	439.2	440.1	438.0	439.8	438.0	10.0	66.8
13°	435.1	437.2	435.7	437.0	434.8	436.6	435.5	10.8	77.5
14°	431.4	434.0	432.4	433.6	431.6	433.2	431.9	11.5	89.0
15°	428.4	430.4	428.4	429.8	427.3	429.7	427.3	12.2	101.2
16°	424.0	426.2	424.9	426.4	423.8	425.9	423.6	12.9	114.0
17°	419.4	422.6	421.1	422.4	419.3	421.8	419.3	13.5	127.5
18°	415.4	418.3	416.6	418.3	414.7	417.9	415.7	14.1	141.7
19°	411.0	414.2	412.3	413.4	410.2	413.1	411.1	14.7	156.4
20°	406.3	409.4	407.5	408.9	405.8	408.8	406.7	15.3	171.7
21°	401.5	404.8	402.9	404.3	400.3	403.5	401.1	15.8	187.5
22°	396.7	399.3	397.7	399.2	395.1	397.8	396.4	16.3	203.8
23°	391.7	394.3	392.2	393.5	390.0	392.7	389.9	16.8	220.7
24°	385.3	388.8	386.1	387.8	384.1	387.0	384.1	17.2	237.9
25°	379.5	382.8	379.6	381.4	378.2	381.1	378.0	17.6	255.5
26°	373.8	376.5	373.2	375.2	371.7	374.0	371.1	18.0	273.5
27°	366.3	369.7	366.2	368.0	364.8	367.8	363.9	18.3	291.7
28°	359.8	362.2	358.8	361.2	358.0	360.2	356.5	18.5	310.3
29°	352.0	355.0	350.9	354.0	350.7	352.8	347.8	18.7	329.0
30°	344.7	347.1	342.9	346.4	342.8	345.3	339.9	18.9	347.9
31°	336.9	339.2	333.9	338.1	336.3	336.6	331.3	19.0	366.9
32°	329.0	330.7	326.0	329.7	328.4	328.6	322.6	19.1	386.0
33°	320.7	322.4	316.9	321.1	320.7	319.7	314.1	19.1	405.0
34°	311.5	313.5	308.1	312.3	312.2	311.4	304.9	19.1	424.1
35°	302.3	304.8	299.5	303.3	303.6	302.2	295.6	19.0	443.1
36°	292.9	295.6	290.2	293.8	294.5	292.6	286.5	18.9	462.0
37°	283.8	286.0	280.7	284.2	285.5	282.8	276.9	18.7	480.7
38°	274.4	275.8	271.2	274.0	276.2	272.6	267.7	18.5	499.1
39°	263.9	264.9	261.3	263.2	266.2	261.4	257.7	18.1	517.3
40°	252.7	253.5	250.1	251.9	256.2	249.6	248.3	17.8	535.0
41°	240.9	240.9	237.7	240.1	245.7	237.1	240.7	17.3	552.3
42°	228.3	228.0	225.7	227.9	233.8	224.4	229.3	16.7	569.1
43°	215.3	215.0	215.4	215.5	222.1	211.6	214.2	16.1	585.2
44°	202.5	201.9	200.4	203.2	209.7	199.8	197.9	15.4	600.6

Photometric test report

Family Round 21 M	Order number: 51MR36ND0421W EAN: 4058352829967	LP number 59653_7
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15°	30°	45°	60°	75°	90° 270°	Phi-zone	Total Phi-zone
		165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°			
Luminous intensity in cd/klm							Luminous flux in lm/klm		
45°	189.7	189.3	186.2	190.9	197.2	187.7	182.5	14.7	615.3
46°	177.4	177.1	173.6	177.8	188.9	175.9	169.9	14.0	629.4
47°	165.4	165.5	159.2	165.5	176.4	164.8	156.7	13.3	642.6
48°	153.8	154.8	148.9	153.7	165.0	154.2	147.7	12.6	655.2
49°	142.7	144.6	140.1	142.4	151.9	144.2	139.0	11.9	667.1
50°	131.1	135.0	132.4	132.1	139.8	134.6	132.6	11.3	678.4
51°	120.2	125.5	126.2	122.6	127.6	125.4	127.3	10.7	689.1
52°	109.1	116.5	119.8	113.6	115.5	116.5	122.2	10.0	699.1
53°	99.0	108.0	113.7	105.3	104.2	108.0	116.1	9.4	708.6
54°	89.9	99.7	107.2	96.9	93.7	99.6	109.3	8.8	717.4
55°	82.2	92.0	100.2	89.5	84.5	91.9	101.5	8.2	725.6
56°	77.9	84.9	92.7	82.4	76.9	84.9	92.5	7.7	733.3
57°	72.6	78.3	85.2	76.3	70.6	78.3	83.7	7.2	740.5
58°	67.4	72.2	77.7	71.1	65.6	72.5	75.4	6.7	747.1
59°	63.6	66.4	70.5	66.5	61.9	67.2	68.1	6.2	753.4
60°	61.0	61.2	63.9	62.3	59.2	62.2	61.8	5.9	759.2
61°	58.8	56.8	58.3	58.6	57.1	58.0	57.0	5.5	764.8
62°	56.4	53.2	53.7	55.3	55.3	54.6	53.0	5.3	770.1
63°	53.3	50.3	50.4	52.3	53.1	51.4	49.9	5.0	775.1
64°	49.8	47.5	48.1	49.0	50.2	48.0	47.7	4.8	779.9
65°	46.0	45.1	46.6	45.6	46.6	44.7	46.0	4.5	784.4
66°	42.4	42.6	45.5	42.3	42.9	41.5	45.4	4.3	788.8
67°	38.8	40.2	44.2	39.1	39.5	38.5	45.0	4.1	792.8
68°	35.5	38.0	42.3	36.4	36.6	36.0	43.6	3.9	796.7
69°	32.8	35.8	39.8	34.2	34.1	34.1	41.0	3.7	800.4
70°	30.8	33.8	37.1	32.9	32.0	32.6	37.9	3.5	803.9
71°	29.4	32.0	34.3	32.1	30.2	31.5	34.9	3.3	807.2
72°	28.5	30.3	31.9	31.0	28.7	30.4	32.2	3.2	810.4
73°	28.0	28.6	30.0	29.4	27.6	29.0	30.0	3.0	813.4
74°	27.7	27.2	28.6	27.5	27.0	27.4	28.4	2.9	816.3
75°	27.2	25.8	27.3	25.6	26.7	25.6	27.0	2.8	819.1
76°	26.4	24.3	25.9	23.9	26.0	24.0	25.8	2.7	821.8
77°	24.7	22.9	24.4	22.4	24.4	22.3	24.3	2.5	824.3
78°	22.4	21.3	22.5	20.9	22.4	20.7	22.7	2.3	826.6
79°	19.9	19.5	20.4	19.1	20.2	19.1	20.8	2.1	828.7
80°	17.5	17.7	18.4	17.3	18.2	17.5	18.7	1.9	830.7
81°	16.1	15.9	16.4	15.6	16.4	15.6	16.6	1.7	832.4
82°	14.7	14.1	14.7	14.0	14.8	13.9	14.5	1.6	834.0
83°	13.4	12.5	13.0	12.4	13.2	12.4	12.6	1.4	835.3
84°	11.9	10.9	11.3	10.8	11.6	10.8	11.0	1.2	836.6
85°	10.4	9.2	9.8	9.2	9.9	9.1	9.5	1.0	837.6
86°	8.8	7.4	8.2	7.5	8.3	7.4	7.9	0.9	838.5
87°	7.3	5.7	6.5	5.7	6.6	5.6	6.3	0.7	839.1
88°	5.0	4.1	4.8	4.2	4.7	4.1	4.7	0.5	839.6
89°	3.1	3.0	3.1	3.2	3.0	3.2	3.0	0.3	840.0

Photometric test report

Family Round 21 M	Order number: 51MR36ND0421W EAN: 4058352829967	LP number 59653_7
----------------------	---	----------------------



Table of values for luminous intensities Maximum luminous intensity

C-planes γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	840.0
91°	5.3	4.7	4.9	4.5	4.6	4.4	4.5	0.5	840.5
92°	6.2	5.5	5.9	5.2	5.6	5.0	5.4	0.6	841.1
93°	6.8	6.2	6.5	6.0	6.3	6.0	6.1	0.7	841.8
94°	7.4	6.9	7.0	6.8	7.0	6.7	6.8	0.8	842.5
95°	7.8	7.4	7.6	7.2	7.6	7.3	7.3	0.8	843.3
96°	8.5	8.2	8.3	7.9	8.3	7.9	7.8	0.9	844.2
97°	9.0	8.7	8.8	8.6	8.8	8.6	8.3	0.9	845.2
98°	9.3	9.2	9.1	9.0	9.2	9.0	8.8	1.0	846.1
99°	9.8	9.7	9.7	9.5	9.6	9.4	9.3	1.0	847.2
100°	10.1	10.2	10.0	9.9	10.0	10.0	9.8	1.1	848.3
101°	10.6	10.5	10.6	10.4	10.5	10.5	10.4	1.1	849.4
102°	11.0	10.9	10.9	10.7	10.9	10.9	10.6	1.2	850.6
103°	11.4	11.3	11.3	11.1	11.4	11.3	11.1	1.2	851.8
104°	11.7	11.7	11.8	11.6	11.7	11.7	11.4	1.2	853.0
105°	12.2	12.1	12.1	12.0	12.2	12.0	11.8	1.3	854.3
106°	12.6	12.4	12.5	12.5	12.6	12.5	12.2	1.3	855.6
107°	12.9	12.8	13.0	12.9	13.0	13.0	12.7	1.4	857.0
108°	13.5	13.3	13.4	13.4	13.4	13.5	13.1	1.4	858.3
109°	14.0	13.8	13.8	13.8	14.0	13.9	13.5	1.4	859.8
110°	14.6	14.3	14.4	14.2	14.5	14.5	14.2	1.5	861.3
111°	15.2	14.8	15.0	14.8	15.0	15.0	14.6	1.5	862.8
112°	15.8	15.5	15.5	15.2	15.4	15.5	15.1	1.6	864.4
113°	16.3	16.0	16.0	15.7	16.0	16.0	15.6	1.6	866.0
114°	17.0	16.5	16.5	16.3	16.6	16.5	16.2	1.7	867.6
115°	17.5	17.1	17.1	17.0	17.2	17.1	16.8	1.7	869.3
116°	18.1	17.5	17.7	17.5	17.8	17.7	17.3	1.7	871.1
117°	18.5	18.1	18.3	18.2	18.3	18.2	18.1	1.8	872.8
118°	19.3	18.7	18.9	18.7	19.0	18.9	18.7	1.8	874.7
119°	20.0	19.3	19.6	19.5	19.7	19.4	19.2	1.9	876.5
120°	20.6	20.0	20.2	20.0	20.1	20.2	20.0	1.9	878.5
121°	21.2	20.7	20.9	20.8	20.9	20.8	20.6	2.0	880.4
122°	22.0	21.3	21.6	21.3	21.6	21.4	21.3	2.0	882.4
123°	22.7	22.1	22.3	22.1	22.3	22.0	21.9	2.0	884.5
124°	23.4	22.8	23.0	22.7	23.2	22.7	22.9	2.1	886.5
125°	24.1	23.5	23.7	23.5	24.0	23.5	23.5	2.1	888.7
126°	25.0	24.3	24.4	24.2	24.8	24.2	24.2	2.2	890.8
127°	25.7	24.9	25.2	25.0	25.6	25.0	25.0	2.2	893.0
128°	26.1	25.8	25.8	25.9	26.5	25.8	26.0	2.2	895.3
129°	26.5	26.6	26.6	26.6	27.3	26.6	26.8	2.3	897.5
130°	27.2	27.4	27.3	27.6	28.1	27.4	27.6	2.3	899.9
131°	28.1	28.4	28.0	28.3	28.8	28.3	28.3	2.3	902.2
132°	28.9	29.2	28.9	29.3	29.5	29.2	29.1	2.4	904.6
133°	29.8	30.2	29.9	30.3	30.3	30.1	30.0	2.4	907.0
134°	30.7	31.1	30.8	31.1	31.2	31.0	30.8	2.4	909.4

Photometric test report

Family Round 21 M	Order number: 51MR36ND0421W EAN: 4058352829967	LP number 59653_7
Table of values for luminous intensities		Maximum luminous intensity
		siteco

C-planes γ	0° 180°	15° 165° 195° 345°	30° 150° 210° 330°	45° 135° 225° 315°	60° 120° 240° 300°	75° 105° 255° 285°	90° 270°	Phi-zone	Total Phi-zone
	Luminous intensity in cd/klm							Luminous flux in lm/klm	
135°	31.6	32.1	31.6	32.1	32.0	32.0	32.0	2.5	911.9
136°	32.6	32.9	32.5	33.0	32.8	32.9	32.9	2.5	914.4
137°	33.6	33.9	33.4	34.0	33.6	33.8	33.7	2.5	916.9
138°	34.7	34.9	34.5	35.0	34.4	34.9	34.6	2.5	919.5
139°	35.7	35.9	35.4	36.0	35.4	35.8	35.7	2.6	922.1
140°	36.6	36.9	36.4	37.1	36.5	36.9	36.7	2.6	924.6
141°	37.5	37.9	37.4	37.9	37.5	38.0	37.7	2.6	927.3
142°	38.5	39.0	38.4	39.1	38.4	39.0	38.8	2.6	929.9
143°	39.4	40.0	39.4	40.3	39.5	40.1	39.6	2.6	932.5
144°	40.5	41.1	40.5	41.3	40.5	41.2	40.6	2.6	935.1
145°	41.4	42.2	41.5	42.5	41.8	42.4	41.7	2.6	937.8
146°	42.5	43.3	42.7	43.5	42.9	43.6	42.9	2.6	940.4
147°	43.7	44.6	43.8	44.9	44.1	44.9	44.0	2.6	943.1
148°	45.0	45.8	45.0	46.1	45.4	46.1	45.3	2.7	945.7
149°	46.2	47.1	46.3	47.4	46.6	47.5	46.5	2.6	948.4
150°	47.6	48.5	47.7	48.8	47.9	48.8	47.9	2.6	951.0
151°	48.8	50.0	49.3	50.4	49.5	50.3	49.5	2.6	953.7
152°	50.3	51.3	50.7	51.9	51.1	51.8	51.0	2.6	956.3
153°	51.9	52.9	52.3	53.5	52.7	53.3	52.7	2.6	958.9
154°	53.6	54.6	53.9	55.0	54.2	54.9	54.2	2.6	961.5
155°	55.4	56.1	55.7	56.6	55.9	56.3	55.5	2.6	964.1
156°	57.3	57.5	57.2	57.8	57.3	57.8	57.1	2.6	966.7
157°	58.8	59.0	58.5	59.1	58.8	59.1	58.7	2.5	969.2
158°	60.1	60.2	59.9	60.3	60.0	60.1	60.1	2.5	971.7
159°	61.1	61.3	60.9	61.3	61.0	61.1	61.1	2.4	974.1
160°	62.1	62.2	61.9	62.0	61.9	61.9	62.0	2.3	976.4
161°	62.8	63.0	62.9	63.0	62.7	62.7	62.7	2.2	978.7
162°	63.5	63.8	63.4	63.7	63.3	63.4	63.3	2.2	980.8
163°	64.1	64.3	64.1	64.1	64.0	64.0	63.7	2.1	982.9
164°	64.7	64.8	64.6	64.7	64.5	64.4	64.1	2.0	984.8
165°	65.2	65.3	65.2	65.2	64.9	65.0	64.7	1.8	986.7
166°	65.7	65.8	65.6	65.7	65.4	65.3	65.1	1.7	988.4
167°	66.1	66.1	66.1	66.0	65.9	65.7	65.5	1.6	990.0
168°	66.6	66.5	66.4	66.4	66.2	66.0	65.8	1.5	991.5
169°	66.8	66.9	66.7	66.7	66.5	66.3	66.1	1.4	992.9
170°	67.1	67.0	66.8	66.9	66.7	66.6	66.4	1.3	994.2
171°	67.3	67.2	67.1	67.2	67.0	66.8	66.6	1.1	995.4
172°	67.5	67.4	67.2	67.3	67.1	66.9	67.0	1.0	996.4
173°	67.5	67.5	67.3	67.4	67.3	66.9	67.0	0.9	997.3
174°	67.7	67.5	67.4	67.6	67.4	67.1	67.3	0.8	998.1
175°	67.6	67.6	67.5	67.5	67.5	67.1	67.4	0.6	998.7
176°	67.5	67.6	67.5	67.5	67.5	67.1	67.4	0.5	999.2
177°	67.5	67.4	67.5	67.3	67.5	67.0	67.4	0.4	999.6
178°	67.4	67.3	67.5	67.4	67.4	67.1	67.5	0.3	999.9
179°	67.4	67.3	67.4	67.4	67.4	67.0	67.4	0.1	1000.0
180°	67.4	67.4	67.4	67.4	67.4	67.4	67.4	0.0	1000.0

Photometric test report

Family Round 21 M	Order number: 51MR36ND0421W EAN: 4058352829967	LP number 59653_7
----------------------	---	----------------------

UGR-Table	Standard room	siteco								
-----------	---------------	--------	--	--	--	--	--	--	--	--

Reflection factor of ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
Reflection factor of walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
Reflection factor of floor	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	View crosswise (C0)					View endwise (C90)					
x	y										
2H	2H	15.9	17.2	16.5	17.7	18.4	15.9	17.2	16.5	17.7	18.4
	3H	16.4	17.5	17.0	18.1	18.8	16.5	17.6	17.1	18.2	18.9
	4H	16.8	17.8	17.4	18.5	19.1	16.9	17.9	17.5	18.5	19.2
	6H	17.2	18.2	17.9	18.8	19.5	17.3	18.2	17.9	18.8	19.5
	8H	17.4	18.2	18.0	18.8	19.6	17.4	18.3	18.1	18.9	19.6
	12H	17.5	18.3	18.2	19.0	19.7	17.6	18.3	18.2	19.0	19.7
4H	2H	16.1	17.1	16.7	17.7	18.4	16.1	17.2	16.7	17.8	18.5
	3H	16.9	17.8	17.6	18.4	19.2	16.9	17.8	17.6	18.4	19.1
	4H	17.4	18.2	18.1	18.8	19.6	17.4	18.2	18.1	18.8	19.6
	6H	18.0	18.6	18.6	19.3	20.1	18.0	18.6	18.6	19.3	20.0
	8H	18.1	18.7	18.8	19.4	20.2	18.1	18.7	18.8	19.4	20.2
	12H	18.4	18.9	19.1	19.6	20.4	18.3	18.8	19.0	19.5	20.3
8H	4H	17.6	18.2	18.3	18.8	19.7	17.6	18.2	18.3	18.8	19.7
	6H	18.2	18.7	18.9	19.4	20.2	18.2	18.7	18.9	19.4	20.2
	8H	18.5	18.9	19.2	19.7	20.5	18.5	18.9	19.2	19.7	20.5
	12H	18.9	19.2	19.6	20.0	20.8	18.8	19.2	19.6	19.9	20.8
12H	4H	17.6	18.2	18.4	18.9	19.7	17.6	18.2	18.4	18.9	19.7
	6H	18.3	18.8	19.1	19.5	20.3	18.3	18.7	19.1	19.5	20.3
	8H	18.7	19.0	19.4	19.8	20.6	18.7	19.0	19.4	19.8	20.6

Luminance table	Max. for $\gamma \geq 65^\circ$	Photometric dimensions in mm: D = 590						
-----------------	---------------------------------	---------------------------------------	--	--	--	--	--	--

C-planes	γ	0° 180°	15°	30°	45°	60°	75°	90°
			165° 195° 345°	150° 210° 330°	135° 225° 315°	120° 240° 300°	105° 255° 285°	270°
Luminance in cd/m²								
45°		7328.8	7313.0	7196.7	7374.9	7620.7	7253.1	7053.2
50°		5574.6	5738.3	5628.5	5614.9	5944.1	5722.5	5635.8
55°		3914.4	4383.8	4774.2	4264.2	4023.6	4378.1	4833.7
60°		3335.9	3346.3	3493.3	3403.7	3233.7	3397.7	3379.1
65°		2973.3	2913.1	3014.1	2950.6	3012.8	2892.4	2975.8
70°		2463.1	2698.9	2960.3	2629.4	2553.4	2603.0	3030.6
75°		2869.4	2728.0	2886.3	2705.8	2819.8	2706.9	2849.4
80°		2757.8	2789.3	2888.6	2723.2	2857.1	2746.8	2937.3
85°		3255.3	2894.8	3079.8	2885.4	3101.7	2857.2	2976.3

Photometric test report

Family Round 21 M	Order number: 51MR36ND0421W EAN: 4058352829967	LP number 59653_7
-----------------------------	---	-----------------------------

Luminance values in cd/m²

γ 65°	γ 70°	γ 75°	γ 80°	γ 85°
--------------	--------------	--------------	--------------	--------------

serial

