

**Order No.:** 51TE1DMN495G | **GTIN (EAN):** 4058352056592


**Product description:** Lic11op,diff,9750lm840,ML,IP54,L1500,wh



Licross® 11 recessed opal MO, luminaire insert, of sheet steel, coil coated, white, length: 1.500mm, width: 76mm, height: 87mm, LED rated luminous flux: 9.750lm, light colour: 840, control gear: ON/OFF Multilumen, with plug, 3-pole, with phase selection, mains connection: 220..240V, AC, 50/60Hz, rated input power: 55W, halogen-free wiring, primary optical cover: cover, of PMMA, light emission: direct with ceiling illumination distribution, primary light characteristic: symmetric, protection rating (complete): IP54, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, UKCA, protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories, impact resistance: IK06, permissible ambient temperature for indoor applications: -35..+40°C, corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting, packaging unit: 1 piece



Lamps:	LED
Wt. (kg):	1.4
GTIN (EAN):	4058352056592



**Order No.:** 51TE1DMN495G | **GTIN (EAN):** 4058352056592

**Detailed technical description:** Lic11op,diff,9750lm840,ML,IP54,L1500,wh



### Key data

- Product type: luminaire insert
- Product name: Licross® 11 recessed opal MO
- Order No.: 51TE1DMN495G

### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Cover: cover, opal
- Beam angle: diffuse distribution
- Symmetry: symmetric
- Light emission: direct with ceiling illumination
- UGR viewing direction along longitudinal luminaire axis:  $\leq 28$
- UGR viewing direction along lateral luminaire axis:  $\leq 28$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 9750lm
- Luminous efficacy: 177lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 55W
- Supplement: halogen-free wiring

#### Operating device:

- Control: ON/OFF Multilumen

### Certificates, Standards

- Protection rating: IP54
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK06
- Protection symbol: D if used in an environment with non-conductive dust loads with corresponding accessories
- Temperature range (operation): -35..+40°C
- Supplement: corresponds to IFS (International Featured Standards) requirements for safety and quality in the food industry, reducing of maximum allowable ambient temperature of 5°C with ceiling mounting
- Certification, designation: CE, ENEC, VDE, UKCA

### Material, Colour

- Licross® LED insert: sheet steel, coil coated, white
- Colour specification: white
- Cover: cover of PMMA

### Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail
- Arrangement: single/continuous arrangement
- Supplement: only suitable for indoor use

### Electrical connection

- Connection: plug, 3-pole, with phase selection
- Nominal voltage: 220..240V, 50/60Hz, AC

### Dimensions, Weight


- Length: 1500mm
- Width: 76mm
- Height: 87mm
- Weight: 1.4kg

### Service life

- Rated service life: 100000h (L80/B50) at AT = ta max, 100000h (L85/B50) at AT = 25°C

Order No.: 51TE1DMN495G | GTIN (EAN): 4058352056592

Dimensions: Lic11op,diff,9750lm840,ML,IP54,L1500,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.de](http://www.siteco.de))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 21.06.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -